

I1 og I2 verdier for Gewiss jordfeilautomater

Jordfeilautomat 2P, B karakteristikk (ref temp 30 °C)

Elnr	A	I1	I2	Forlegning		Kabel mm ²
				A1	A2	
1612731	10A	1,13	1,40	Ok	Ok	1,5 mm ²
1612732	13A	1,13	1,42	Ok	Ok	2,5 mm ²
1611899	15A	1,13	1,30	Ok	-	2,5 mm ²
1612733	16A	1,13	1,45	-	-	2,5 mm ²
1612733	16A	1,13	1,45	Ok	Ok	4,0 mm ²
1612734	20A	1,13	1,30	Ok	-	4,0 mm ²
1612735	25A	1,13	1,45			
1612736	32A	1,13	1,45			

Jordfeilautomat 2P, C karakteristikk (ref temp 30 °C)

Elnr	A	I1	I2	Forlegning		Kabel mm ²
				A1	A2	
1606401	10A	1,13	1,40	Ok	Ok	1,5 mm ²
1612723	13A	1,13	1,42	Ok	Ok	2,5 mm ²
1611898	15A	1,13	1,30	Ok	-	2,5 mm ²
1606402	16A	1,13	1,45	-	-	2,5 mm ²
1606402	16A	1,13	1,45	Ok	Ok	4,0 mm ²
1606403	20A	1,13	1,30	Ok	-	4,0 mm ²
1606404	25A	1,13	1,45			
1606405	32A	1,13	1,45			

Jordfeilautomat 3P, MDC100. C karakteristikk (ref temp 30 °C)

				Forlegning		
Elnr	A	I1	I2	A1	A2	Kabel mm ²
1606453	10A	1,13	1,45	Ok	-	1,5 mm ²
1606453	10A	1,13	1,45	Ok	Ok	2,5 mm ²
1606454	16A	1,13	1,43	Ok	Ok	4,0 mm ²
1606455	20A	1,13	1,45	Ok	Ok	6,0 mm ²
1606456	25A	1,13	1,45			
1606457	32A	1,13	1,45			